NSN 5305-01-234-7550

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-234-7550 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.170 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Head Surface Treatment:** Paint **Special Features:** Head color gray per federal standard 595 no. 6231; furnished with boot type nylon washer, 0.312 outside dia **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization:

NSN 5305-01-234-7550

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.