

View Online at <https://aerobasegroup.com/nsn/5305-01-234-7575>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.874 inches and 1.062 inches

**Fastener Length:**

Between 2.406 inches and 2.500 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.195 inches and 0.211 inches

**Width Between Flats:**

Between 0.489 inches and 0.500 inches

**Hole Diameter:**

Between 0.060 inches and 0.068 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

45.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Material:**

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025 or steel comp 1026 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Or Standard:**

2 type and 10p style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0