NSN 5305-01-235-3145

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-235-3145 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 0.922 inches and 0.954 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.562 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.230 inches and 0.240 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.553 inches and 0.573 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 203ez or steel comp 303 or steel comp 303se or steel comp 303ma or steel comp 303cu or steel comp 303 plus x or steel comp 416 or steel comp 416se or steel comp 416 plus x or steel comp 430f or steel comp 430fse **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-235-3145

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0