

View Online at <https://aerobasegroup.com/nsn/5305-01-236-0313>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.208 inches

Fastener Length:

0.312 inches

Head Style:

Pan

Head Diameter:

Between 0.205 inches and 0.219 inches

Head Height:

Between 0.070 inches and 0.080 inches

Locking Feature:

Locking teeth threads

First Diameter From Head:

Between 0.0925 inches and 0.1120 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.108 inches

Internal Drive Style:

Cross recess type 1

End Application:

M60a3 tank tts

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

480 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Special Features:

Thd relieved to 0.0925 in. Min diameter to 0.1120 in. Maximum diameter from bearing surface of head for 1/3 of lg towards screw point

Material:

Stainless steel

Material Specification:

Ed-std-66 federal standard 5th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 4 federal specification single treatment response

Thread Series Designator:

Unc

Fsc Application Data:

Periscope subassembly

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0