

View Online at <https://aerobasegroup.com/nsn/5305-01-236-0313>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.208 inches

**Fastener Length:**

0.312 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.205 inches and 0.219 inches

**Head Height:**

Between 0.070 inches and 0.080 inches

**Locking Feature:**

Locking teeth threads

**First Diameter From Head:**

Between 0.0925 inches and 0.1120 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.108 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

M60a3 tank tts

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

480 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Thd relieved to 0.0925 in. Min diameter to 0.1120 in. Maximum diameter from bearing surface of head for 1/3 of lg towards screw point

**Material:**

Stainless steel

**Material Specification:**

Ed-std-66 federal standard 5th material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 4 federal specification single treatment response

**Thread Series Designator:**

Unc

**Fsc Application Data:**

Periscope subassembly

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0