NSN 5305-01-236-1610

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-1610 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.657 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.270 inches **Head Height:** Between 0.088 inches and 0.102 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 24.0 rockwell c and 35.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate Qq-p-416 type 2 class 2 federal specification single treatment response

Screw Surface Treatment Specification: Thread Series Designator: Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-236-1610

Machine Screw - Page 2 of 2



Fiig:

A500d0