NSN 5305-01-236-1628

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-1628

3a Thread Direction: Right-hand Thread Length: 1.125 inches Fastener Length: Between 1.460 inches and 1.500 inches Head Style: Filt channfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pallet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches With Across Flats: Between 0.520 inches and 0.253 inches Thready Qay Per Inch (tpl): 18 Min. Tonsile Strength (psi): 16000 pounds per square inch Material: Platic polyamide locking feature Material: Platic polyamide locking feature Material And Location: silver Pacious Material: Platic rotament: Silver Pacious Material: Baterial Freatment: Platic rotament: Platic polyamide locking le	
Right-hand Thread Length: 1.125 inches Fastener Length: Between 1.460 inches and 1.500 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpl): 18 Min Tensile Strength (psi): 160000 pounds per square inch Material: Platic polyamide locking feature Material Specification: Niver Precious Material: Silver Precious Material: Silver Precious Material: Silver	
Thread Length: 1.125 inches Fastener Length: 1.125 inches Fastener Length: Between 1.460 inches and 1.500 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.469 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Platic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard	
1.125 inches Fastener Length: Between 1.460 inches and 1.500 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 asın standard single material response fastener or ams 5737 asın standard single material response Precious Material: Silver Precious Material: Silver Surface Treatment: Passivate fastener	
Fastener Length: Between 1.460 inches and 1.500 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or selip threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material: Plastic polyamide locking feature Material: Precious Material And Location: silver Silver Precious Material: Pacious Material: Pacious Material: Pacious Material: Silver Precious Material: Silver Pacious Material: Pacious Material: Pacous Materia	
Between 1.460 inches and 1.500 inches Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Platic polyamide locking feature Material: Silver Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Head Style: Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material: Silver Precious Material And Location: silver Precious Material: Silver Precious Material: Silver Precious Material: Silver Precious Material: Silver	
Flat chamfer Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: ass 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Precious Material: Silver Precious Material: Silver Pasivate fastener	
Head Diameter: Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material: Plastic polyamide locking feature Material: Precious Material single material response fastener or ams 5737 assn standard single material response Precious Material: silver Precious Material: </td <td></td>	
Between 0.457 inches and 0.469 inches Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material: Silver Precious Material: Silver Precious Material: Silver Precious Material: Silver Surface Treatment: Passivate fastener	
Head Height: Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Platic polyamide locking feature Material Specification: Arris 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material: silver Precious Material: Silver Precious Material: Silver Precious Material: Silver Patrial: Silver Patrial: Silver Passivate fastener	
Between 0.306 inches and 0.312 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material: Silver Precious Material: Silver Surface Treatment: Passivate fastener	
Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Thread Diameter: 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Sufface Treatment: Passivate fastener	
Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
18 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
160000 pounds per square inch Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Material: Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Plastic polyamide locking feature Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Material Specification: Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
Precious Material And Location: silver Precious Material: Silver Surface Treatment: Passivate fastener	
silver Precious Material: Silver Surface Treatment: Passivate fastener	se fastene
Precious Material: Silver Surface Treatment: Passivate fastener	
Silver Surface Treatment: Passivate fastener	
Surface Treatment: Passivate fastener	
Passivate fastener	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response fastener	
Thread Series Designator:	
Unrc	
Specification Data:	

NSN 5305-01-236-1628

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

