NSN 5305-01-236-1655

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-1655 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.815 inches and 2.000 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.740 inches and 0.750 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Surface Finish: 63.0 microinches grip Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-236-1655

Socket Head Cap Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0