## NSN 5305-01-236-1664

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-1664

| View Online at https://aerobasegroup.com/nsn/5305-01-236-1664                                      |
|--|
| Thread Class:  |
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 1.125 inches   |
| Fastener Length:   |
| Between 1.210 inches and 1.250 inches  |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.457 inches and 0.469 inches  |
| Head Height:   |
| Between 0.306 inches and 0.312 inches  |
| Internal Drive Style:  |
| Hexagon  |
| Thread Diameter:   |
| 0.312 inches   |
| Width Across Flats:  |
| Between 0.250 inches and 0.253 inches  |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unrc   |
| Specification Data:  |
| 80205-nas1352 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

No

## NSN 5305-01-236-1664

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

