NSN 5305-01-236-1678

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5305-01-236-1676
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.338 inches and 0.388 inches
Fastener Length:
Between 0.848 inches and 0.878 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.360 inches and 0.374 inches
Head Height:
Between 0.115 inches and 0.125 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
63.0 microinches bearing surface of head
Special Features:
Internal drive ribbed
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf

Specification Data:

80205-nas1578 professional/industrial association standard

NSN 5305-01-236-1678

Close Tolerance Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0