## NSN 5305-01-236-1680

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-1680 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.614 inches and 0.664 inches **Fastener Length:** Between 1.312 inches and 1.342 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** sponse

Qq-p-35 federal specification single treatment res
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-236-1680

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0