

View Online at <https://aerobasegroup.com/nsn/5305-01-236-1682>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.296 inches and 0.328 inches

Fastener Length:

Between 0.962 inches and 1.068 inches

Head Style:

Fillister

Head Diameter:

Between 0.280 inches and 0.320 inches

Head Height:

Between 0.118 inches and 0.130 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.119 inches and 0.131 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

70000 pounds per square inch

Material:

Steel comp 302 spring or steel comp 302b spring or steel comp 304 spring or steel comp 304l spring or steel comp 305 spring or steel comp 308 spring or steel comp 309 spring or steel comp 309s spring or steel comp 310s spring or steel comp 314 spring or steel comp 316 spring or steel comp 316l spring or steel comp 317 spring or steel comp 321 spring or steel comp 347 spring or steel comp 348 spring or steel comp 403 spring or steel comp 405 spring or steel comp 410 spring or steel comp 414 spring or steel comp 420 spring or steel comp 430 spring or steel comp 431 spring or steel comp 440a spring or steel comp 440b spring or steel comp 440c spring or steel comp 446 spring

Material Specification:

Qq-s-763 federal specification all material responses stand-off

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: