

View Online at <https://aerobasegroup.com/nsn/5305-01-236-2212>

Fastener Length:

Between 1.450 inches and 1.500 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.195 inches and 0.225 inches

Internal Drive Style:

Cross recess type 1

Nonmachine Thread Style:

Wood screw (type wd)

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Nonmachine Thread Diameter:

0.112 inches

Material:

Steel comp 1010 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1108 or steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response or mil-c-81562, type 2, class 3 military specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 2nd treatment response or mil-c-81562, type 2, class 3 military specification 2nd treatment response

Specification Or Standard:

1 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.