NSN 5305-01-236-2551

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-2551
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.251 inches and 0.301 inches
Fastener Length:
Between 1.449 inches and 1.479 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unif

Specification Data:

80205-nas1123 professional/industrial association standard

NSN 5305-01-236-2551

Close Tolerance Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Shelf Life:

Mil-std (military Standard): Mil-s-5626 spec.