

View Online at <https://aerobasegroup.com/nsn/5305-01-236-6193>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 1.892 inches and 1.922 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.3898 inches and 0.3948 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.428 inches and 1.448 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Countersink Angle:**

101.0 degrees

**Special Features:**

Finish top of head with white paint, color no. 37875 per fed-std-595

**Material:**

Steel comp xm-13

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c-83488, type 2, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.