Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-236-6990

tion enine at https://doi/obdo	
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.178 inches and 0.1	98 inches
Fastener Length:	
Between 0.423 inches and 0.4	53 inches
Head Style:	
Fillister	
Head Diameter:	
Between 0.167 inches and 0.1	77 inches
Head Height:	
Between 0.069 inches and 0.0	79 inches
First Diameter From Head:	
Between 0.073 inches and 0.0	83 inches
Distance From Largest Bear	ing Surface Of Head To End Of First Diameter:
Between 0.240 inches and 0.2	60 inches
Internal Drive Style:	
Slot	
Thread Diameter:	
0.112 inches	
Thready Qty Per Inch (tpi):	
40	
Externally Relieved Body Dia	ameter Quantity:
1	
Material:	
Steel comp 203ez or steel cor	np 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303pb or steel comp 303se or stee
comp 416 or steel comp 416 p	blus x or steel comp 416se or steel comp 430f or steel comp 430fse or steel comp 420f or steel comp
420fse or steel comp 440f	
Surface Treatment:	
Passivate	
Surface Treatment Specifica	tion:
Qq-p-35 federal specification s	ingle treatment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	