NSN 5305-01-236-7086

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-236-7086 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.086 inches and 0.096 inches **Fastener Length:** 0.250 inches **Head Style:** Pan **Head Diameter:** Between 0.155 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches **First Diameter From Head:** Between 0.056 inches and 0.060 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.159 inches **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 00-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-236-7086

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0