NSN 5305-01-237-2681

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-237-2681 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.869 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.442 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp 302b or steel comp 303 plus x or steel comp 303cu or steel comp 303se **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response Color: Black **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 3c style Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A500d0

Demilitarization:

NSN 5305-01-237-2681

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.