

View Online at <https://aerobasegroup.com/nsn/5305-01-237-2788>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.295 inches and 0.300 inches

**Fastener Length:**

0.687 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.419 inches and 0.437 inches

**Head Height:**

Between 0.122 inches and 0.132 inches

**Locking Feature:**

Strip threads

**First Diameter From Head:**

0.185 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.387 inches and 0.392 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.1562 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unrf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0