NSN 5305-01-237-4178



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-237-4178 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.338 inches and 0.381 inches **Head Height:** Between 0.039 inches and 0.041 inches **Shoulder Diameter:** 0.2021 inches first shoulder and 0.2026 inches first shoulder **Shoulder Length:** 0.6467 inches first shoulder and 0.6487 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Cetyl alcohol lube Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf

Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
-Demilitarization:

No

NSN 5305-01-237-4178 Shoulder Screw - Page 2 of 2



Fiig:

A003b0