## NSN 5305-01-237-4994



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-237-4994 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.147 inches and 0.221 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.156 inches and 0.172 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 class 2 military specification single treatment response Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-237-4994

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.