NSN 5305-01-237-6836

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-237-6836



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.283 inches and 0.375 inches

Fastener Length:

Between 0.345 inches and 0.375 inches

Head Style:

Pan

Head Diameter:

Between 0.495 inches and 0.505 inches

Head Height:

Between 0.174 inches and 0.184 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Steel comp 4140 or steel comp 8740 or steel comp e4340

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-5000 military

specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Special Features:

Furnished with boot type nylon washer; color of washer black per federal standard 595 no. 27038

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-237-6836

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5626 spec.

