## NSN 5305-01-237-6840

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-237-6840 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.347 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.477 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 2910 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Stainless steel **Screw Material Specification:** Qq-s-763 federal specification single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 96906-ms51960 government standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A500d0

## NSN 5305-01-237-6840

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.