## NSN 5305-01-237-9316

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-237-9316

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.203 inches
Fastener Length:
Between 0.582 inches and 0.612 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.231 inches and 0.323 inches
Internal Drive Style:
Slot
Material Accommodated Thickness:
Between 0.313 inches and 0.375 inches
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Navy special project
Material:
Steel comp 304 stand-off
Material Specification:
Mil-a-23195 military specification single material response stand-off
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5305-01-237-9316

Panel Screw Assembly - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-a-23195 spec.

