NSN 5305-01-237-9316

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-237-9316 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** Between 0.582 inches and 0.612 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.231 inches and 0.323 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.313 inches and 0.375 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel comp 304 stand-off **Material Specification:** Mil-a-23195 military specification single material response stand-off **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-237-9316

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-23195 spec.