Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-237-9364
Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
Between 0.408 inches and 0.500 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Plastic polyamide locking feature
Material Specification:
Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-237-9364

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

