

View Online at <https://aerobasegroup.com/nsn/5305-01-237-9377>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.271 inches and 0.281 inches

Fastener Length:

Between 0.573 inches and 0.603 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.221 inches and 0.226 inches

Head Height:

Between 0.074 inches and 0.086 inches

Grip Diameter:

Between 0.1365 inches and 0.1375 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.138 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1121 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.