

View Online at <https://aerobasegroup.com/nsn/5305-01-238-0605>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.782 inches and 0.875 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.238 inches and 0.279 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp 302b or steel comp 303 plus x or steel comp 303cu or steel comp 303se

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 class 4 military specification single treatment response

Color:

Black

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 3c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.