NSN 5305-01-238-0609

Thread Class:

N/a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-238-0609

| За |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.214 inches and 0.307 inches |
| Fastener Length: |
| Between 0.344 inches and 0.375 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.270 inches and 0.332 inches |
| Locking Feature: |
| Strip threads |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 24.0 rockwell c and 35.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1189 professional/industrial association standard |
| Shelf Life: |

NSN 5305-01-238-0609

Socket Head Cap Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0