NSN 5305-01-239-0641

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-0641

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.615 inches and 0.682 inches
Fastener Length:
Between 1.250 inches and 1.297 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.755 inches and 0.760 inches
Head Height:
Between 0.101 inches and 0.103 inches
Shoulder Diameter:
0.4052 inches first shoulder and 0.4057 inches first shoulder
Shoulder Length:
0.615 inches first shoulder and 0.635 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-239-0641

Shoulder Screw - Page 2 of 2



em			

No

Fiig:

A003b0