NSN 5305-01-239-0642

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-0642

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.442 inches and 0.510 inches
Fastener Length:
Between 1.640 inches and 1.688 inches
Head Style:
Flat countersunk undercut
Head Diameter:
Between 0.501 inches and 0.506 inches
Head Height:
Between 0.058 inches and 0.060 inches
Shoulder Diameter:
0.2802 inches first shoulder and 0.2807 inches first shoulder
Shoulder Length:
1.178 inches first shoulder and 1.198 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
100.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-239-0642

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0