NSN 5305-01-239-1325

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-1325 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.505 inches and 0.572 inches **Fastener Length:** Between 1.890 inches and 1.937 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.628 inches and 0.633 inches **Head Height:** Between 0.074 inches and 0.076 inches **Shoulder Diameter:** 0.3427 inches first shoulder and 0.3432 inches first shoulder **Shoulder Length:** 1.365 inches first shoulder and 1.385 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnish with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-239-1325

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0