NSN 5305-01-239-1515

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-1515 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.443 inches and 0.510 inches **Fastener Length:** Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.501 inches and 0.506 inches **Head Height:** Between 0.058 inches and 0.060 inches **Shoulder Diameter:** 0.2802 inches first shoulder and 0.2807 inches first shoulder **Shoulder Length:** 0.615 inches first shoulder and 0.635 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnish with one o-ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-239-1515

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0