

View Online at <https://aerobasegroup.com/nsn/5305-01-239-3498>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.212 inches

Fastener Length:

Between 0.907 inches and 0.969 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.296 inches and 0.328 inches

Head Height:

Between 0.296 inches and 0.328 inches

Point Length:

0.094 inches

Point Diameter:

Between 0.104 inches and 0.120 inches

First Diameter From Head:

Between 0.115 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.632 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

90.0 degrees

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

UNF

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0