

View Online at <https://aerobasegroup.com/nsn/5305-01-239-3518>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.459 inches and 0.479 inches

Fastener Length:

Between 0.615 inches and 0.635 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

Between 0.305 inches and 0.314 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Width Across Flats:

0.125 inches

Thready Qty Per Inch (tpi):

32

Special Features:

Slot through shank, 0.044 in. Min 0.054 in. Maximum width and 0.545 in. Long

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 317 or steel comp 321 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0