NSN 5305-01-239-5068

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-5068 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.831 inches and 0.863 inches **Fastener Length:** Between 1.081 inches and 1.113 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 165000 pounds per square inch Hardness Rating: 37.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unf

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-239-5068

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0