NSN 5305-01-239-5912

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-5912

| Inread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.337 inches and 0.387 inches |
| Fastener Length: |
| Between 0.534 inches and 0.564 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.177 inches and 0.197 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches threads |
| Special Features: |
| Internal drive ribbed |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single |
| material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2 class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |

_ ...

Specification Data:

80205-nas1578 professional/industrial association standard

NSN 5305-01-239-5912

Close Tolerance Screw - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0