NSN 5305-01-239-9395

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-239-9395 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.390 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.557 inches and 0.577 inches **Head Height:** Between 0.235 inches and 0.265 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** Material: Aluminum **Surface Treatment:** Chromate **Surface Treatment Specification:** Mil-I-5541 class 1a military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-239-9395

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-I-5541 spec.