# NSN 5305-01-240-1264

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-240-1264



#### **Thread Class:**

2a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.345 inches and 0.438 inches

## Fastener Length:

Between 0.407 inches and 0.438 inches

## Head Style:

Flat countersunk

# Head Diameter:

Between 0.238 inches and 0.279 inches

# Internal Drive Style:

Cross recess type 1

# Thread Diameter:

0.138 inches

# Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

80000 pounds per square inch

## Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316

## Head Surface Treatment:

Plastic epoxy

## Shank Surface Treatment:

Passivate

## Head Surface Treatment Specification:

Mil-c-22750, class 1, type 2 military specification single treatment response

## Shank Surface Treatment Specification:

Astm a380-78 assn standard single treatment response

#### **Special Features:**

Color no. 26555 per federal standard 595

#### **Thread Series Designator:**

Unc

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-240-1264

Machine Screw - Page 2 of 2

**Fiig:** A500d0

Mil-std (military Standard):

Mil-c-22750 spec.

