## NSN 5305-01-240-1786

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-240-1786 **Thread Direction:** Right-hand Thread Length: Between 2.7 millimeters and 2.9 millimeters **Fastener Length:** Between 8.03 millimeters and 8.18 millimeters **Head Style:** Flat chamfer **Head Diameter:** Between 5.5 millimeters and 5.8 millimeters **Head Height:** Between 1.7 millimeters and 1.9 millimeters First Diameter From Head: Between 2.0 millimeters and 2.1 millimeters Distance From Largest Bearing Surface Of Head To End Of First Diameter: 5.3 millimeters **Internal Drive Style:** Slot **Thread Diameter:** 3.0 millimeters **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class: Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 416 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-240-1786

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0