Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-240-1786

Thread Dir	ection:
Right-hand	
Thread Lei	ngth:
Between 2.	7 millimeters and 2.9 millimeters
Fastener L	ength:
Between 8.	03 millimeters and 8.18 millimeters
Head Style	:
Flat chamfe	r
Head Diam	eter:
Between 5.	5 millimeters and 5.8 millimeters
Head Heig	ht:
Between 1.	7 millimeters and 1.9 millimeters
First Diam	eter From Head:
Between 2.	0 millimeters and 2.1 millimeters
Distance F	rom Largest Bearing Surface Of Head To End Of First Diameter:
5.3 millimet	ers
Internal Dr	ive Style:
Slot	
Thread Dia	meter:
3.0 millimet	ers
Thread Pite	ch In Millimeters:
0.5	
External T	nread Tolerance Class:
6g	
Externally	Relieved Body Diameter Quantity:
1	
Material:	
Steel comp	416
Material Sp	pecification:
Astm a582	assn standard single material response
Surface Tr	eatment:
Passivate	
Surface Tr	eatment Specification:
Qq-p-35 fee	deral specification single treatment response
Thread Se	ies Designator:
М	
Shelf Life:	
N/a	
Unit Of Me	asure:
Demilitariz	ation:
No	

NSN 5305-01-240-1786

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

