NSN 5305-01-240-2658

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-240-2658 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.491 inches and 0.541 inches **Fastener Length:** Between 1.001 inches and 1.031 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Shoulder Diameter:** 0.4052 inches first shoulder and 0.4057 inches first shoulder **Shoulder Length:** 0.333 inches first shoulder and 0.373 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Internal hexagon socket in threaded end 0.1582 in. Min and 0.1617 in. Maximum width across flats Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-240-2658

Shoulder Screw - Page 2 of 2



Fiig:

A003b0