NSN 5305-01-240-4026

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-240-4026 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.682 inches **Fastener Length:** Between 1.125 inches and 1.172 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.755 inches and 0.760 inches **Shoulder Diameter:** 0.4052 inches first shoulder and 0.4057 inches first shoulder **Shoulder Length:** 0.490 inches first shoulder and 0.510 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Supply with o ring per st7m251 Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

NSN 5305-01-240-4026

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0