

View Online at <https://aerobasegroup.com/nsn/5305-01-240-5173>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.376 inches and 0.438 inches

**Fastener Length:**

0.438 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.285 inches and 0.332 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Navy special project

**Screw Material:**

Steel comp 302 and steel comp 303 and steel comp 304

**Screw Material Specification:**

66 federal standard single material response

**Screw Surface Treatment:**

Primer and enamel lusterless

**Screw Surface Treatment Specification:**

Mil-p-15328 military specification 1st treatment response and 595, 36231 federal standard 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-p-15328 spec.