# NSN 5305-01-240-5173

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-240-5173



# **Thread Class:**

2a

**Thread Direction:** 

Right-hand

# Thread Length:

Between 0.376 inches and 0.438 inches

#### Fastener Length:

0.438 inches

#### Head Style:

Flat countersunk

#### Head Diameter:

Between 0.285 inches and 0.332 inches

#### Internal Drive Style:

Cross recess type 1

# Thread Diameter:

0.164 inches

#### Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

80000 pounds per square inch

## Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### **Product Name:**

Navy special project

Screw Material:

Steel comp 302 and steel comp 303 and steel comp 304

#### **Screw Material Specification:**

66 federal standard single material response

#### Screw Surface Treatment:

Primer and enamel lusterless

#### Screw Surface Treatment Specification:

Mil-p-15328 military specification 1st treatment response and 595, 36231 federal standard 2nd treatment response

#### **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A500d0

# NSN 5305-01-240-5173

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-p-15328 spec.

