NSN 5305-01-240-5184

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-240-5184 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 1.579 inches and 1.609 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.377 inches and 0.381 inches **Head Height:** Between 0.043 inches and 0.045 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Furnished with rubber o-ring Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488 type 2 cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-240-5184

Close Tolerance Screw - Page 2 of 2



U	nit	Of	Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.