

View Online at <https://aerobasegroup.com/nsn/5305-01-240-7386>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.813 inches and 0.875 inches

**Fastener Length:**

0.875 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.202 inches and 0.212 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Screw Material:**

Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Special Features:**

Extension on threaded end 0.100 in. Lth, 0.090 in. Dia; concentric hole in extension 0.070 in. Diameter and 0.050 in. Lth

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0