## NSN 5305-01-241-0751

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-0751 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.123 inches and 0.212 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.207 inches and 0.225 inches **Head Height:** Between 0.038 inches and 0.047 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl 4 military specification single treatment response Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-241-0751

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.