## NSN 5305-01-241-0756

Between 0.505 inches and 0.572 inches

Between 1.515 inches and 1.562 inches

**Thread Class:** 

Right-hand

**Thread Direction:** 

Thread Length:

Fastener Length:

Flat countersunk undercut

**Head Style:** 

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-241-0756

Head Diameter:
Between 0.629 inches and 0.634 inches
Head Height:
Between 0.088 inches and 0.090 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.312 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Furnished with one o-ring; cetyl alcohol lubricant
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf

## NSN 5305-01-241-0756

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0