

View Online at <https://aerobasegroup.com/nsn/5305-01-241-0757>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.614 inches and 0.681 inches

Fastener Length:

Between 1.812 inches and 1.859 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.756 inches and 0.760 inches

Head Height:

Between 0.115 inches and 0.116 inches

Grip Diameter:

Between 0.3740 inches and 0.3745 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Grip Length:

Between 1.178 inches and 1.198 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Furnished with one o-ring; cetyl alcohol lubricant

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0